

PL/PDF

PL/PDF Tag
User's Guide
v2.1.0

Contents

Introduction	1
Procedures	2
Stored tags	2
Init	2
SetStyle	2
PrintText	2
PrintFlowingText	3
PrintFlowingTextLimit	3

Introduction

PL/PDF Tag package is an extension for PL/PDF, which allows to write tag-formatted text to the PDF document. It can work only with PL/PDF v2.1.0 or higher.

Procedures

Stored tags

Stored tags means a set of records, which was defined by procedure `PLPDF_TAG.SetStyle`. The text could be formatted with these tags. There are two kind of tags: style-tag and command-tag. Style-tags contains any text formatting settings, for example font size or font family.

Format: `<tag_name>...</tag_name>`.

Command-tags contains any PL/SQL block.

Format: `<tag_name/>`.

There is one built in command-tag, named `
`(Break line).

Init

Type: Procedure

Description: Initialize the package variables and delete all stored tags(except `
`).

Version: v1.0.0

Parameters: -

Return: -

SetStyle

Type: Procedure

Description: Create a new stored-tag. The parameter `p_spec` decides between two types. When `p_spec` is 0, then family, style, size, color will be apply. In the other case, when `p_spec` is 1, then only `p_command` will be apply.

Version: v1.0.0

Parameters:

- `p_name` varchar2: Name of the new tag.
- `p_family` varchar2 default 'CURRENT': Font type. *CURRENT*: current font.
- `p_style` varchar2 default 'CRR': Font style.
 - o CRR: current style
 - o null: Regular
 - o B: Bold
 - o I: Italic
 - o U: Underline
 - o The styles may be combined (i.e. BI will be Bold and Italic).
- `p_size` number default -1.: Font size. -1: current size.
- `p_color` plpdf_type.t_color default NULL,: Sets the text color for objects inserted after this statement.
- `p_spec` number default 0: Type of the tag.
 - o 0: style-tag
 - o 1: command-tag
- `p_command` varchar2 default null: PL/SQL block.

Return: -

PrintText

Type: Procedure

Description: Put tag-formatted text into the current page. This procedure don't know the
 command-tag.

Version: v1.0.0

Parameters:

- p_x number: X coordinate of text.
- p_y number: Y coordinate of text.
- p_txt: Tag-formatted text.

Return: -

PrintFlowingText

Type: Procedure

Description: Prints tag-formatted text continuously. Text is wrapped according to the right margin.

Version: v1.0.0

Parameters:

- p_h number default 0: Height.
- p_txt varchar2 default null: Text.
- p_link varchar2 default null: URL or internal link ID.
- p_align varchar2 default null: Text alignment.
 - o L: Left
 - o R: Right
 - o C: Center
 - o J: Force Justification

Return: -

PrintFlowingTextLimit

Type: Procedure

Description: Prints tag-formatted text continuously. Text is wrapped according to the p_min_x and p_max_x.

Version: v1.0.0

Parameters:

- p_h number default 0: Height.
- p_txt varchar2 default null: Text.
- p_link varchar2 default null: URL or internal link ID.
- p_min_x number default 0: min X position, 0 means the limit is the left margin.
- p_max_x number default 0: max X position, 0 means the limit is the right margin.
- p_align varchar2 default null: Text alignment.
 - o L: Left
 - o R: Right
 - o C: Center
 - o J: Force Justification

Return: -